






Specification sheet

PVE 900 STAGE V / TIER 4F

Hydraulic Power Pack

English



Specifications :

PVE 900 STAGE V / TIER 4F




Diesel Engine	CAT C18	
Max. theoretical power	563/755	kW/HP
Max. frequency	1800	rpm
Max. operating pressure	350	bar
Hydraulic pump	Parker	
Max. oil flow	972	L/min
Diesel oil	1100	L
DEF (AdBlue) capacity	N.A.	L
Hydraulic oil	2265	L
Weight without fuel	9320	kg
Weight filled up	10250	kg



Technische Daten PVE 900 STAGE V / TIER 4F

Aggregat

Deutsch



Technische Daten :

PVE 900 STAGE V / TIER 4F




Dieselmotor	CAT C18	
Max. theoretische Leistung	563/755	kW/HP
Max. Drehzahl	1800	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Parker	
Max. Fördermenge	972	L/min
Diesel Öl	1100	L
DAF (AdBlue) kapazität	N.A.	L
Hydraulische Öl	2265	L
Gewicht ohne Diesel Öl	9320	kg
Gewicht	10250	kg

Spécifications

PVE 900 STAGE V / TIER 4F

Groupe hydraulique

Français



Spécifications

PVE 900 STAGE V / TIER 4F




Moteur Diesel	CAT C18	
Puissance théorique max.	563/755	kW/HP
Max. fréquence	1800	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Parker	
Débit d'huile max.	972	L/min
Huile diesel	1100	L
Capacité FED (AdBlue)	N.A.	L
Huile hydraulique	2265	L
Poids sans huile diesel	9320	kg
Poids	10250	kg

Specificaties

PVE 900 STAGE V / TIER 4F

Hydraulisch aggregaat

Nederlands



Specificaties

PVE 900 STAGE V / TIER 4F

Dieselmotor	CAT C18	
Max. theoretisch vermogen	563/755	kW/HP
Max. toerental	1800	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Parker	
Max. olie doorstroming	972	L/min
Diesel olie	1100	L
DEF (AdBlue) capaciteit	N.A.	L
Hydraulische olie	2265	L
Gewicht zonder diesel	9320	kg
Gewicht	10250	kg






Specificatii

PVE 900 STAGE V / TIER 4F

Unitate de alimentare

Español



Specificatii

PVE 900 STAGE V / TIER 4F

Motor diesel	CAT C18	
Putere max. teoretica	563/755	kW/HP
Frecventa max.	1800	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Parker	
Debit max. de ulei	972	L/min
Ulei Diesel	1100	L
Capacitate DEF (AdBlue) N.A.		L
Ulei hidraulic	2265	L
Greutate fara ulei	9320	kg
Greutate	10250	kg






Specifications

PVE 900 STAGE V / TIER 4F

Hydraulic Power Pack

USA

Dimensions in inches



Specifications

PVE 900 STAGE V / TIER 4F

Diesel Engine	CAT C18	
Max. theoretical power	563/755	kW/HP
Max. frequency	1,800	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Parker	
Max. oil flow	257	gal/min
Diesel Fuel	291	gal
DEF (AdBlue) capacity	N.A.	gal
Hydraulic oil	598	gal
Weight without fuel	20,547	lbs
Weight with fuel	22,597	lbs