


**Robust grabs for excavators with revolutionary exchange system in a single device. As a new demand on site arises, the attachment can be exchanged and the new application can commence. Easy remounting of shells for excavating, landscaping, laying pipes, logging, rail track handling etc.**

- ▷ **Efficiency:** only the shells are replaced; exchange is possible with only one person
- ▷ **Fastness:** easy exchange of the lynch pin from the change-over system within 4 minutes, no hydraulic work necessary
- ▷ **Robust technics:** compact design through the integrated rotator. Robust shell bearing with coexisting change mechanism




**Clamshell buckets with exchangeable shells are available for**

- ▷ excavators up to 8t/17600lbs: C08VE / T08VE / R08VE and more
- ▷ excavators up to 12t/26400lbs: C12VE / T12VE / R12VE and more

Rock tines



Clamshell bucket



Foundation shells



Well shaft shells



Pipe grab



Module



Timber tines



Rail tines



Hay and forestry tines

Start



Close bucket and set it down. Mount the exchange support.

0,58 min.



Remove the lynch pin from the change-over system.

1,67 min.



Remove the change-over pin with extraction tool.

2,50 min.



Position the bucket carrier over the new attachment and close the locking unit hydraulically.

3,75 min.



Insert the change-over pin and fasten the lynch pin.

4 min. ready!



Remove the exchange support. Ready for use!