

Mounting options for Earth Drills

Single pin hitches

Type	for earth drills	with pin Ø (mm/in)	for operating weight (t/lbs)
KM 501-X1500-4500MAX-25	X1500 - 4500MAX	25 / 0.9	1-5 / 2200-11000
KM 501-X1500-4500MAX-30	X1500 - 4500MAX	30 / 1.1	1-5 / 2200-11000
KM 501-X1500-4500MAX-32	X1500 - 4500MAX	32 / 1.2	1-5 / 2200-11000
KM 501-X1500-4500MAX-35	X1500 - 4500MAX	35 / 1.3	1-5 / 2200-11000
KM 501-X1500-4500MAX-38	X1500 - 4500MAX	38 / 1.4	1-5 / 2200-11000
KM 501-X1500-4500MAX-40	X1500 - 4500MAX	40 / 1.5	1-5 / 2200-11000
KM 501-7000MAX-8000MAX-40	7000MAX / 8000MAX	40 / 1.5	4,5-8 / 9900-17600 & loader
KM 501-7000MAX-8000MAX-44,5	7000MAX / 8000MAX	44,5 / 1.7	4,5-8 / 9900-17600 & loader
KM 501-7000MAX-8000MAX-45	7000MAX / 8000MAX	45 / 1.7	4,5-8 / 9900-17600 & loader
KM 501-7000MAX-8000MAX-50	7000MAX / 8000MAX	50 / 1.9	4,5-8 / 9900-17600 & loader
KM 501-7000MAX-8000MAX-55	7000MAX / 8000MAX	55 / 2.1	4,5-8 / 9900-17600 & loader
KM 501-7000MAX-8000MAX-60	7000MAX / 8000MAX	60 / 2.3	4,5-8 / 9900-17600 & loader
KM 501-15000MAX-25000MAX-44,5	15000MAX	44,5 / 1.7	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-45	15000MAX	45 / 1.7	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-50	15000MAX	50 / 1.9	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-55	15000MAX	55 / 2.1	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-60	15000MAX	60 / 2.3	8-22 / 17600-48400



Cardan link with system L-Lock

Type	for earth drills	with adapter	for operating weight (t/lbs)
KSW01-X1500	X1500	KSW01	1-2 / 2200-4400
KSW01-X2000	X2000	KSW01	1-2,5 / 2200-5500
KSW03-X2500	X2500	KSW03	1,5-3 / 3300-6600
KSW03-3000MAX	3000MAX	KSW03	2-4 / 4400-8800
KSW03-3500MAX	3500MAX	KSW03	2,5-4,5 / 5500-9900
KSW03-4500MAX	4500MAX	KSW03	3-5 / 6600-11000
KSW03-7000MAX	7000MAX	KSW03	5-7 / 11000-15400 & loader
KSW08-7000MAX	7000MAX	KSW08	5-7 / 11000-15400 & loader
KSW08-8000MAX	8000MAX	KSW08	6-8 / 13200-17600
KSW10-15000MAX	15000MAX	KSW10	10-15 / 22000-33000



Cradle hitch with system L-Lock

Type	for earth drills	with adapter	for operating weight (t/lbs)
KSW01-X1500 Cradle	X1500	KSW01	1-2 / 2200-4400
KSW01-X2000 Cradle	X2000	KSW01	1-2,5 / 2200-5500
KSW03-X2500 Cradle	X2500	KSW03	1,5-3 / 3300-6600
KSW03-3000MAX Cradle	3000MAX	KSW03	2-4 / 4400-8800
KSW03-3500MAX Cradle	3500MAX	KSW03	2,5-4,5 / 5500-9900
KSW03-4500MAX Cradle	4500MAX	KSW03	3-5 / 6600-11000
KSW03-7000MAX Cradle	7000MAX	KSW03	5-7 / 11000-15400 & loader
KSW08-7000MAX Cradle	7000MAX	KSW08	5-7 / 11000-15400 & loader
KSW08-8000MAX Cradle	8000MAX	KSW08	6-8 / 13200-17600
KSW10-15000MAX Cradle	15000MAX	KSW10	10-15 / 22000-33000



Lower part of hitch for specific solution

Type	for earth drills	for operating weight (t/lbs)
KM 691-X2000-8000MAX	X2000 to 8000MAX	1-8 / 2200-17600 & loader
KM 691-15000MAX-25000MAX	15000MAX	10-15 / 22000-33000



Lower part of cradle hitch for specific solution

Type	for earth drills	for operating weight (t/lbs)
KM 691-X2000-X2500 Cradle	X2000 to X2500	1,5-3 / 3300-6600
KM 691-3000MAX-4500MAX Cradle	3000MAX to 4500MAX	2-5 / 4400-11000
KM 691-7000MAX-8000MAX Cradle	7000MAX and 8000MAX	5-8 / 11000-17600 & loader
KM 691-15000MAX Cradle	15000MAX	10-15 / 22000-33000



Mounting options for Earth Drills

Ein-Bolzen-Aufhängungen

Typ	für Erdbohrer	mit Bolzen Ø (mm/in)	für Dienstgewicht (t/lbs)
KM 501-15000MAX-25000MAX-44,5	15000MAX bis 25000MAX	44,5 / 1.7	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-45	15000MAX bis 25000MAX	45 / 1.8	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-50	15000MAX bis 25000MAX	50 / 2	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-55	15000MAX bis 25000MAX	55 / 2.2	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-60	15000MAX bis 25000MAX	60 / 2.4	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-65	15000MAX bis 25000MAX	65 / 2.6	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-70	15000MAX bis 25000MAX	70 / 2.8	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-75	15000MAX bis 25000MAX	75 / 3	8-22 / 17600-48400
KM 501-15000MAX-25000MAX-80	15000MAX bis 25000MAX	80 / 3.1	8-22 / 17600-48400
KM 501-35000MAX-65000MAX-60	35000MAX bis 65000MAX	60 / 2.4	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-65	35000MAX bis 65000MAX	65 / 2.6	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-70	35000MAX bis 65000MAX	70 / 2.8	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-75	35000MAX bis 65000MAX	75 / 3	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-80	35000MAX bis 65000MAX	80 / 3.1	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-90	35000MAX bis 65000MAX	90 / 3.5	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-100	35000MAX bis 65000MAX	100 / 3.9	20-45 / 44000-96800
KM 501-35000MAX-65000MAX-110	35000MAX bis 65000MAX	110 / 4.3	20-45 / 44000-96800



Aufhängungen mit Anschweissadapter für System L-Lock

Typ	für Erdbohrer	mit Adapter	für Dienstgewicht (t/lbs)
KSW10-15000MAX	15000MAX	KSW10	10-15 / 22000-33000
KSW10-20000MAX	20000MAX	KSW10	13-20 / 28600-44000
KSW21-25000MAX	25000MAX	KSW21/25	15-22 / 33000-48400
KSW21-35000MAX	35000MAX	KSW21/25	20-45 / 44000-96800
KSW21-42000MAX	42000MAX	KSW21/25	20-45 / 44000-96800
KSW21-65000MAX	65000MAX	KSW21/25	21-45 / 46200-96800



Aufhängungen mit Auflage und Anschweissadapter für System L-Lock

Typ	für Erdbohrer	mit Adapter	für Dienstgewicht (t/lbs.)
KSW10-15000MAX Cradle	15000MAX	KSW10	10-15 / 22000-33000
KSW10-20000MAX Cradle	20000MAX	KSW10	13-20 / 28600-44000
KSW21-25000MAX Cradle	25000MAX	KSW21/25	15-22 / 33000-48400



Aufhängungsunterteile für Eigenlösung

Typ	für Erdbohrer	für Dienstgewicht (t/lbs)
KM 691-15000MAX-25000MAX	15000MAX bis 25000MAX	10-22 / 22000-48400
KM 691-35000MAX-65000MAX	35000MAX bis 65000MAX	20-45 / 44000-94800



Aufhängungsunterteile mit Auflage für Eigenlösung

Typ	Für Erdbohrer	für Dienstgewicht (t/lbs)
KM 691-15000MAX Cradle	15000MAX	10-15 / 22000-33000
KM 691-20000MAX-25000MAX Cradle	20000MAX bis 25000MAX	13-22 / 28600-48400

