

The KM 626HPX with the *HPXdrive Standard* for digging and handling, is due to its size ideal for small cranes. The revolutionary *HPXdrive* technology guarantees a reliable and virtually maintenance free attachment.

- ▷ **Reliability** of the HPXdrive! The movement of the arms of the grapple is generated by two hollow shafts, which run opposed and have a helix thread, hydraulically driven by a single piston. No more hydraulic cylinder.
- ▷ **Longer life cycle** up to 50%! The drive unit runs in a permanent oil bath – no lubrication service is necessary. The compact design makes the HPXdrive resistant to dirt and debris.
- ▷ **Versatility** with different types of shells that can easily be refitted onto the driving unit.
- ▷ **Profitability** through low maintenance costs and longer life cycle.
- ▷ **Precise handling** with the gear-type KINSHOFER rotator and shells synchronised by the single piston turning both shafts.
- ▷ **Rotator** with shaft is available as an alternative, in case a quick change to a non-rotating hook is favoured.
- ▷ **Constant closing force** (6820 lbf at 3750 psi operating pressure) for the entire opening and closing process.



Package Clamshell Bucket KM 626HPX with KINSHOFER Flange Rotator									
Type	Volume	Width A	Height	max. Opening	Number of teeth	Self weight	Closing force	Load capacity	
	(c.y.)	(in)	(in)	(in)		(lbs)	(lbf)	(lbs)	
KM 626HPX-95 c	0.12	16	30	35	4	550	6820	4400	
KM 626HPX-100 c	0.13	18	30	35	4	561	6820	4400	
KM 626HPX-150 c	0.20	24	30	35	6	616	6820	4400	

Package consists of: clamshell bucket, bolt-on teeth, rotator KM 04 F140-30V, upper suspension KM 501 4500, pressure relief valve, non-return valve

Please note:
 - the KM 626HPX is also available with a shaft rotator and quick change system KM 505
 - for heavy duty tasks we recommend to use quick change KM 505 HD with rotator KM 04 S68-30US

Package Clamshell Bucket KM 626HPX/502 with KINSHOFER Rotator with Shaft and Reduction Link									
Type	Volume	Width A	Height	max. Opening	Number of teeth	Self weight	Closing force	Load capacity	
	(c.y.)	(in)	(in)	(in)		(lbs)	(lbf)	(lbs)	
KM 626HPX-95/502 c	0.12	16	32.5	35	4	561	6820	4400	
KM 626HPX-100/502 c	0.13	18	32.5	35	4	572	6820	4400	
KM 626HPX-150/502 c	0.20	24	32.5	35	6	627	6820	4400	

Package consists of: clamshell bucket, bolt-on teeth, rotator KM 04 S, reduction link KM 502 4500, short connecting hoses KM 203 01, upper suspension KM 501 4500, pressure relief valve, non-return valve

Accessories

Type	Description
KM 680 02	scraper
KM 685 05	adapters for compression rails
KM 685 06 HPX SD	central lifting device
KM 685 07 set	wear plates to protect horizontal cutting edges (2 pieces)
KM 204 01	mobile part of hydraulic quick coupling for hose (Ø 0.4 in, 2 pieces)
KM 204 02	fixed part of hydraulic quick coupling for rotator (Ø 0.4 in, 2 pieces)

Requirements of Truck Crane

Operating pressure at oil flow:

3750 psi at max. 20 GPM
 2900 - 5350 psi at max. 10.5 GPM

Technical Drawings

