

The reliable asymmetric orange peel grapple KM 652/2 with half closing tines provides for an easy transport, resting flat against the crane arm and not protruding the width of the carrier machine. It is mainly used for handling scrap, waste and construction materials, and is available with five (KM 652-5/2) or six tines (KM 652-6/2) - depending on the task.

- ▷ **Asymmetric construction:** the grapple rests flat against the crane arm in its transport position (see below drawing).
- ▷ **Special slot on the main carrier** allows the transport of a big orange peel grapple, that does not protrude the width of the carrier (2,5 m).
- ▷ **Half closing tines** by default, completely closing at the points, for handling waste, scrap, loose materials, etc.
- ▷ **Non-return valve** guarantees a secure retention of loads even when pressure drops.
- ▷ **Long service life** due to robust design - oil distributor and hydraulic hoses are protected in the center part, generously dimensioned bearings, wear-resistant shells made of 400 HB steel, cylinder with piston rod protection, stops for both end positions of tines.
- ▷ **Strong operation** due to high closing forces (13 kN at 26 MPa operating pressure).



Asymmetric orange peel grapples KM 652-5/2 and KM 652-6/2

Type	Number of tines	Volume (litre)	Opening \varnothing A (mm)	Width E (closed) (mm)	Height C (mm)	Weight (w/o rotator) (kg)	Capacity (kg)	Closing force (kN)
KM 652-5/2	5	240	1790	1065	1110	350	2500	13
KM 652-6/2	6	240	1790	1065	1110	410	2500	13

Package consists of: orange peel grapple, non-return valve

Accessories

Type	Description
KM 06 F173-35	recommended KINSHOFER rotator for KM 652/2

Requirements of truck crane

Operating pressure at oil flow:

max. 26 MPa (260 bar) at 25 - max. 75 l/min

⚠ **Mind the pressure!**

Technical drawings

