

The **KINSHOFER** container discharge unit with twin-hook for deposit containers with system Schäfer are characterised by short cycle times and an attractive acquisition price. Containers can be emptied even faster and more cost effectively with a one-man operation. The attachment is extremely maintenance low, robust and low-built thanks to its compact construction.

Container discharge unit KM 920-31 for containers with twin-hook system

- ▷ **Robust mechanics.**
- ▷ **Precise positioning** with KINSHOFER rotator, short hose connection.
- ▷ **Independence of crane operating pressure** due to the pressure relief valve.
- ▷ Easy handling thanks to **low overall height.**
- ▷ **Low maintenance.**



Type	Lift of the hook max. A (mm)	Width E (mm)	Width D (mm)	Load capacity (kg)	Height C (mm)	Self weight* (kg)
KM 920-31	500	805	265	4500	615	160

* incl. rotator & hoses / excl. upper suspension & pendulum damper

Package consists of: container discharge unit, rotator KM 04 F, short connecting hoses KM 203 01, upper suspension with pendulum damper KM 511 (4500), pressure relief valve and non-return valve

Requirements of truck crane

Operating pressure (open/close):	max. 35 MPa (350 bar)
Recommended oil flow (open/close):	40 l/min
Operating pressure (rotation):	max. 26 MPa (260 bar)
Recommended oil flow (rotation):	25 - max. 75 l/min

Technical drawings

