

The robust 4-finger timber grab unifies the proven KINSHOFER rotator with sturdy logging tines for excavators with up to 12t/26400lbs operating weight. Ideal also for forestry enterprises handling windfalls or when realizing special demolition or pile foundation tasks.

- ▷ The kinematics of the tines **avoid the unintended clamping of material.**
- ▷ **Logs with 110mm/4.3in to 590mm/23.2in in diameter** can be gripped.
- ▷ **Robust, fully integrated rotation with two motors. Integrated pressure relief valve against overcharge.**
- ▷ **High closing force** achieved by two hydraulic cylinders. **Robust bearings** are made for high forces.



Timber Grab T12H

Type	Width E (mm/in)	Opening A (mm/in)	Height C min. (mm/in)	Log-Ø (mm/in)	Volume (m ³ /cord)	Weight (kg/lbs)	Load capacity (kg/lbs)	Closing force (kN/lbf)
T12H-60	600 / 23.6	1850 / 72.8	1135 / 44.6	110-590 / 4.3-23.2	0,40 / 0.27	610 / 1342	3000 / 6600	16 / 3520

Package consists of: timber grab, **KINSHOFER** rotation and non-return valve

Accessories

Type	Description
KM 690 15t	adapter for rigid mounting – up to 15t/33000lbs
KSW08 rigid	bolt-on adapter for system L-Lock KMS08L/KHS08L for rigid mounting – up to 12t/26400lbs
OQ45/4 rigid	bolt-on adapter for OilQuick OQ45 – up to 12t/26400lbs
	adapters for quick change systems from other manufacturers or different sizes on request

Requirements of carrier machine

Operating pressure (open/close):	max. 28 MPa (280 bar) / 4060 psi
Operating pressure (rotate):	14 - 25 MPa (140 - 250 bar) / 2030 - 3620 psi
Recommended pump capacity (rotate):	25 - 75 l/min / 6.5 - 20 GPM

Technical drawing

