

Lifting, moving and positioning of palletized or unpalletized materials is easy with the GAF Fork Set. Turn your excavator into a fork lift truck - ideal in combination with a Tiltrotator. Now also available with hydraulically adjustable tines for an even easier and more effective and secure working.

- ▷ **High load capacity.**
- ▷ **Low self-weight.**
- ▷ **Very economic:** low cost.
- ▷ **Ideal for use with Tiltrotator:** highest flexibility.
- ▷ **Two versions available: with mechanically or hydraulically adjustable tines.**
- ▷ **Easy mounting** thanks to a quick change adapter.
- ▷ **Different adapters** available.
- ▷ **Mechanical fork tines with adapter system L-Lock, Oilquick or Verachtert** without surcharge.



Mechanic Fork Tines GAF

Type	for NOX	Standard connection	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAF6	TR06NOX / TR07NOX	S40	1900 / 4180	1000 / 39.3	140 / 308	1000 / 39.3	3 - 6 / 6600 - 13200
GAF8	TR07NOX / TR11NOX	S45	1900 / 4180	1200 / 47.2	190 / 418	1000 / 39.3	6 - 8 / 13200 - 17600
GAF12	TR11NOX	S45	2500 / 5500	1200 / 47.2	200 / 440	1200 / 47.2	9 - 12 / 19800 - 26400

Package consists of: fork tines, frame with standard suspension for S-couplers*

Hydraulic Fork Tines GAH

Type	for NOX	Standard connection	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAH6	TR06NOX / TR07NOX	S40	1900 / 4180	1000 / 39.3	160 / 352	1000 / 39.3	3 - 6 / 6600 - 13200
GAH8	TR07NOX / TR11NOX	S45	1900 / 4180	1200 / 47.2	210 / 462	1000 / 39.3	6 - 8 / 13200 - 17600
GAH12	TR11NOX	S45	2500 / 5500	1200 / 47.2	220 / 484	1200 / 47.2	9 - 12 / 19800 - 26400

Package consists of: hydraulic fork tines, frame with standard suspension for S-couplers*

*other adapters available on request

Note: put loads always the nearest to the back and to the centre of gravity

Requirements for carrier machine



The excavator must be conform to lifting regulations

Pictures



Hydraulically adjustable fork tines here with fully hydraulic OQ-quick change adapter



Hydraulically adjustable fork tines here with cylinderless **NOX** Tiltrotator

Lifting, moving and positioning of palletized or unpalletized materials is easy with the GAF or GAH Fork Set. Turn your excavator into a fork lift truck - ideal in combination with a Tiltrotator. Now also available with hydraulically adjustable tines for an even easier and more effective and secure working.

- ▷ High load capacity.
- ▷ Low self-weight.
- ▷ Very economic: low cost.
- ▷ Ideal for use with Tiltrotator: highest flexibility.
- ▷ Two versions available: with mechanically or hydraulically adjustable tines.
- ▷ Easy mounting thanks to a quick change adapter.
- ▷ Different adapters available.
- ▷ Mechanical fork tines with adapter system L-Lock, Oilquick or Verachtert without surcharge.



Mechanic Fork Tines GAF

Type	for NOX	Standard adapter	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAF18	TR14NOX / TR19NOX	S45 S60	4000 / 8800	1200 / 47.2	340 / 748	1200 / 47.2	13-18 / 28600-39600
GAF20	TR19NOX / TR25NOX	S70	4000 / 8800	1200 / 47.2	420 / 924	1200 / 47.2	19-20 / 41800-44000
GAF24	TR25NOX	S70	5000 / 11000	1200 / 47.2	440 / 968	1200 / 47.2	21-24 / 46200-52800

Package consists of: fork tines, frame with standard suspension for S-couplers*

Hydraulic Fork Tines GAF

Type	for NOX	Standard adapter	Load capacity max. (kg/lbs)	Width (mm/in)	Weight (kg/lbs)	Tine length (mm/in)	Operating weight (t/lbs)
GAH18	TR14NOX / TR19NOX	S45 S60	4000 / 8800	1200 / 47.2	340 / 748	1200 / 47.2	13-18 / 28600-39600
GAH20	TR19NOX / TR25NOX	S70	4000 / 8800	1200 / 47.2	420 / 924	1200 / 47.2	19-20 / 41800-44000
GAH24	TR25NOX	S70	5000 / 11000	1200 / 47.2	440 / 968	1200 / 47.2	21-24 / 46200-52800

Package consists of: hydraulic fork tines, frame with standard suspension for S-couplers*

*other adapters available on request

Note: put loads always the nearest to the back and to the centre of gravity

Requirements for carrier machine



The excavator must conform to lifting regulations

Pictures



Hydraulically adjustable fork tines here with fully hydraulic OQ-quick change adapter

Hydraulically adjustable fork tines here with cylinderless **NOX** Tiltrotator